HIGH PERFORMANCE DISTRIBUTED COMPUTING PROGRAM (HiPer-D)

ENGINEERING TESTBED TWO A (T2A) REPORT

DECEMBER 16, 1997

NAVAL SEA SYSTEMS COMMAND

NSWC

Naval Surface Warfare Center

DAHLGREN DIVISION

Panama City Dahlgren

TABLE OF CONTENTS

SECTION **PAGE**

EXECUTIVE SUMMARY 1

1.0 INTRODUCTION 3
1.1 Background 3
1.1.1 Phase I Integrated Demonstration One (I1) 3
1.1.2 The HiPer-D Phase 2 Engineering Test and Demonstration Plan 4
1.1.3 HiPer-D Engineering Testbed 4
1.1.4 HiPer-D Engineering Test Bed One (T1) 6
1.1.5 HiPer-D Engineering Test Bed Two (T2) 6
1.2 T2A Goals and Objectives 7
1.2.1 Critical Issues Mapping 11

2.0 STAND-ALONE ENGINEERING TESTS 13
2.1 Stand-Alone Network Tests 13
2.1.1 Distributing Time-Sensitive Data in a COTS Shared Media Environment 13
2.2 Time Services in HiPer-D T2A 14

3.0 INTEGRATED DEMONSTRATION DESCRIPTION 15
3.1 Functional Description 15
3.1.1 Tracking Correlation and Filtering (TCF) 15
3.1.2 Air Engagement Control (AEC) 18
3.1.2.1 AEC Component Descriptions 18
3.1.3 Track Data Services Components 21
3.1.4 Support Components for T2A 23
3.1.5 Resource Management 26
3.1.6 Clock Synchronization 26
3.1.7 Near Real-Time Data Collection/Display 27
3.1.8 Post Run Data Analysis/Display 27
3.1.9 Commercial Off-The-Shelf (COTS) Software 29
3.2 T2A Hardware Configuration 29
3.3 T2A Computer Program Configuration 31
3.4 T2A Scenario and Description 31
3.4.1 Location 31
3.4.2 Stand-Alone GDCsim Demonstration 33
3.4.3 Integrated System Demonstration 33
3.4.3.1 One-Button Start-up 33
3.4.3.2 Dynamic Resource Allocation 34
3.4.3.3 Fault/Restart RTDS Server 34
3.4.3.4 Fault/Restart Auto-Special Peer Client 34
3.4.3.5 CDK Display Integration 35

3.4.3.6 GDCsim/WCS (GDC client) High Data Rate Demonstration 35
3.4.3.7 Sensor Rate Server Demonstration 35
3.4.3.8 Auto-Special Engagements 36
3.4.3.9 GoPlot Performance Displays 36
3.5 System Performance Analysis 36
3.5.1 Jewel Near Real-Time Data Extraction Displays 37
3.5.1.1 Track Load Client Display 37
3.5.1.2 Multiple Auto-Special Peer Clients Display 37
3.5.1.3 Gyro Data Converter Simulator Display 41
3.5.2 IMP Displays 43
3.5.2.1 RTDS IMP Display 43
3.5.2.2 Auto-SM IMP Display 45
3.5.3 GoPlot System Component Performance Displays 45

4.0 T2A ACCOMPLISHMENTS SUMMARY 50
4.1 Increase Track Capacity 50
4.2 Compare Network Technologies 50
4.3 Achieve Software Portability in a Heterogeneous Environment 53
4.3.1 Vendor Unique Compiler Interfaces 53
4.3.2 Operating System Interfaces 54
4.3.3 Data Design 55
4.3.4 Summary 57
4.4 Add Resource Management 57
4.5 Improved Data Management 59
4.5.1 Improved High Data Rate Distribution - GDCsim and GDC Client 59
4.5.2 Improved Management of Track Data Rates 62
4.6 Integrate CDK Display into HiPer-D 68
4.7 HiPer-D Time Synchronization 71
4.8 Instrumentation and Measurement Capability Enhanced 71
4.9 One Button Start-up 72
4.10 Other Lessons Learned 73
4.10.1 CDK/HiPer-D Interface 73
4.10.2 Track Data Services 73
4.10.3 GDCSim Lessons Learned 75
4.10.4 Resource Management Lessons Learned 76
4.10.5 Additional COTS Lessons Learned 76

APPENDIXES

A - Stand-Alone Network Testing in HiPer-D
B - Time Services in HiPer-D T2A
C - Gyro Data Converter (GDC) Experiment